

CANON EF LENS SPECIFICATIONS	Apparent Focal length (mm)		Focus Drive	Angle of View (Diagonal)			Lens Construction (Groups/Elements)	Minimum Aperture (f)	Filter Diameter (mm)	Closest Focusing Distance		Length		Weight		Lens Hood	Lens Cap	Soft Case			
	APS-C	APS-H		35mm	APS-C	APS-H				(ft.)	(m)	(in.)	(mm)	(oz.)	(g)						
	Ultra-Wide Zoom																				
• EF5 10-22mm f/3.5-4.5 USM ††	16–35	N/A	Ultrasonic	N/A	107°30'–63°30'	N/A	10/13	22	77	0.8	0.24	3–1/2	89.8	13.6	385	EW-83E	E-77U	LP1319			
• EF16-35mm f/2.8L II USM	26–56	21–45	Ultrasonic	108°10'–63°	68°9'–39°41'	86°–50°	12/16	22	82	0.92	0.28	4–2/5	111.6	22.4	635	EW-88	E-82U	LP1319			
• EF16-35mm f/2.8L USM †	26–56	21–45	Ultrasonic	108°10'–63°	68°9'–39°41'	86°–50°	10/14	22	77	0.9	0.28	4–1/8	103.1	13.3 lbs.	600	EW-83E	E-77U	LP1319			
• EF17-35mm f/2.8L USM †	–	–	Ultrasonic	–	–	–	–	–	–	10/15	22	77	1.38	0.42	3–3/4	95.7	19.1	545	EW-83C	E-77U	–
• EF17-40mm f/4L USM	27–64	22–52	Ultrasonic	104°–57°30'	65°54'–36°13'	83°12'–46°	9/12	22	77	0.92	0.28	3–3/4	96.8	1.1 lbs.	475	EW-83E	E-77U	LP1319			
• EF20-35mm f/2.8 USM †	–	–	AFD	–	–	–	12/15	22	72	1.6	0.5	3–1/2	89.0	1.2 lbs.	540	EW-75	–	–			
• EF20-35mm f/3.5-4.5 USM †	32–56	26–46	Ultrasonic	94°–63°	59°13'–39°41'	75°12'–50°24'	11/12	22-27	77	1.1	0.34	2–3/4	88.9	11.9	340	EW-83I	E-77U	LP1214			
Standard Zoom																					
• EF5 17-55mm f/2.8 IS USM ††	27–88	N/A	Ultrasonic	N/A	78°30'–27°50'	N/A	12/19	22	77	1.5	0.35	4–2/5	110.6	22.8	645	EW-83J	E-77U	–			
• EF5 17-85mm f/4.5-6.3 IS USM ††	27–136	N/A	Ultrasonic	N/A	78°30'–18°25'	N/A	12/17	22	67	1.1	0.35	3–5/8	92.0	1.1 lbs.	475	EW-73B	E-67U	LP1116			
• EF5 18-55mm f/3.5-5.6 IS ††	29–88	N/A	MM	N/A	74°20'–27°50'	N/A	9/11	22	58	0.82	0.25	2–3/4	68.5	7.8	200	EW-60C	E-58	LP814			
• EF5 18-55mm f/3.5-5.6 USM †	29–88	N/A	Ultrasonic	N/A	74°20'–27°50'	N/A	9/11	22-38	58	0.92	0.28	2–5/8	66.2	6.7	190	EW-60C	E-58U	LP814			
• EF5 18-55mm f/3.5-5.6 *****	29–88	N/A	MM	N/A	74°20'–27°50'	N/A	9/11	22-38	58	0.92	0.28	2–5/8	66.2	6.7	190	EW-60C	E-58U	LP814			
• EF22-55mm f/4-5.6 USM †	–	–	Ultrasonic	–	–	–	9/9	22–32	58	–	0.35	–	–	–	175	–	–	–			
• EF24-70mm f/2.8L USM	38–112	31–91	Ultrasonic	84°–34°	52°55'–21°25'	67°12'–27°12'	13/16	22	77	1.25	0.38	4–7/8	123.5	2.1 lbs.	950	EW-83F	E-77U	LP1219			
• EF24-85mm f/3.5-4.5 USM †	38–136	31–111	Ultrasonic	84°–28°30'	52°55'–17°57'	67°12'–22°48'	12/15	22–32	67	1.6	0.5	2–3/4	69.5	1.34	380	EW-73II	E-67U	LP1014			
• EF24-105mm f/4L IS USM	38–168	31–136	Ultrasonic	84°–23°20'	52°55'–14°40'	67°12'–18°24'	13/18	22–27	77	1.5	0.45	3–5/16	83.5	1.5 lbs.	670	EW-83H	E-77U	LP1219			
• EF28-70mm f/2.8L USM †	–	–	Ultrasonic	–	–	–	11/16	22	77	1.6	0.5	4–5/8	116.7	1.9 lbs.	880	EW-83B	E-77U	–			
• EF28-70mm f/3.5-4.5 †	–	–	MM	–	–	–	9/10	29	52	–	0.39	–	–	–	300	–	–	–			
• EF28-90mm f/3.5-5.6 V USM†/V USM†	45–128	36–104	Ultrasonic	75°–30°	47°15'–18°54'	60°–24°	10/10	22–38	58	1.25	0.38	2–13/16	71.2	7.8	200	EW-60C	E-58	LP814			
• EF28-80mm f/3.5-5.6 III †/II †	45–128	36–104	MM	75°–30°	47°15'–18°54'	60°–24°	10/10	22–38	58	1.25	0.38	2–13/16	71.2	7.8	200	EW-60C	E-58	LP814			
• EF28-80mm f/3.5-5.6 †	45–128	36–104	MM	75°–30°	47°15'–18°54'	60°–24°	10/10	22–38	58	1.25	0.38	2–13/16	71.2	7.8	200	EW-60C	E-58	LP814			
• EF28-90mm f/4-5.6 III †/II USM	45–144	36–117	MM/Ultrasonic	75°–27°	47°15'–17°	60°–21°36'	8/10	22–32	58	1.3	0.38	2–13/16	71.0	6.7	190	EW-60C	E-58U/E-58	LP814			
• EF28-90mm f/4-5.6 USM †	45–144	36–117	Ultrasonic	75°–27°	47°15'–17°	60°–21°36'	10/10	22–32	58	1.3	0.38	2–13/16	71.0	6.7	190	EW-60C	E-58	LP814			
• EF28-105mm f/3.5-4.5 II USM / USM †	45–168	36–136	Ultrasonic	75°–23°20'	47°15'–14°40'	60°–18°24'	12/15	22–27	58	1.6	0.5	3	75.0	1.31	375	EW-63II	E-58U	LP814			
• EF28-105mm f/4-5.6 USM †	45–168	36–136	Ultrasonic	75°–23°20'	47°15'–14°40'	60°–18°24'	10/10	22–32	58	1.57	0.48	2–11/16	68.0	7.4	210	EW-63B	E-58U	LP814			
• EF28-135mm f/3.5-5.6 IS USM	42–216	36–176	Ultrasonic	75°–18°	47°15'–11°20'	60°–14°24'	12/16	22–36	72	1.64	0.5	3–13/16	96.8	1.2 lbs.	540	EW-78BII	E-72U	LP1116			
• EF28-200mm f/3.5-5.6 USM	45–320	36–260	Ultrasonic	75°–12°	47°15'–7°34'	60°–9°36'	12/16	22–36	72	1.5	0.45	3–1/2	89.6	1.1 lbs.	500	EW-78D	E-72U	LP1116			
• EF35-80mm f/4-5.6 III †/II / USM †	56–128	46–104	MM	63°–30°	39°41'–18°54'	50°24'–24°	8/8	22–32	52	1.3	0.4	2–1/2	63.5	6.2	175	EW-54B	E-52	LP814			
• EF35-135mm f/4-5.6 USM †	–	–	Ultrasonic	–	–	–	12/14	22–32	58	2.5	0.75	3–3/8	86.0	15.0	425	EW-62	–	–			
Telephoto Zoom																					
• EF28-300mm f/3.5-5.6L IS USM	45–480	36–390	Ultrasonic	75°–8°15'	47°15'–5°24'	60°–6°36'	16/22	38	77	2.3	0.7	7–1/4	184.0	3.7 lbs.	1,670	EW-83G	E-77U	LZ1324			
• EF35-350mm f/3.5-5.6 USM †	–	–	Ultrasonic	–	–	–	15/21	22–32	72	2.0	0.6	6–9/16	167.0	3.0 lbs.	1,385	EW-78	E-72U	–			
• EF55-200mm f/4-5.6 II USM †/ USM †	88–320	72–260	Ultrasonic	72–260	27°5'–7°34'	34°24'–9°36'	13/13	22–29	52	3.9	1.2	3–13/16	97.3	10.9	310	ET-54	E-52U	LP1016			
• EF55-250mm f/4-5.6 IS †	88–400	N/A	DC motor	N/A	27°5'–6°15'	N/A	10/12	22–32	58	3.6	1.1	4.3	108	15.4	390	ET-60	E-58	LP1019			
• EF70-200mm f/2.8L IS USM / USM †	112–320	91–260	Ultrasonic	34°–12°	21°15'–7°34'	27°12'–9°36'	18/23	32	77	4.6	1.4	7–13/16	197.0	3.2 lbs.	1,470	ET-86	E-77U	LZ1324			
• EF70-200mm f/4L IS USM	112–320	91–260	Ultrasonic	34°–12°	21°15'–7°34'	27°12'–9°36'	15/20	32	67	3.9	1.2	6–7/8	172.0	26.8	760	ET-74	E-67U	LP1224			
• EF70-200mm f/4L USM	112–320	91–260	Ultrasonic	34°–12°	21°15'–7°34'	27°12'–9°36'	13/16	32	67	3.9	1.2	6–7/8	172.0	19.2	705	ET-74	E-67U	LP1224			
• EF70-300mm f/4-5.6 DO IS USM	112–480	91–390	Ultrasonic	34°–8°15'	21°15'–5°24'	27°12'–6°36'	12/18	32–38	58	4.6	1.4	3–7/8	99.0	1.6 lbs.	720	ET-65B	E-58U	LP1116			
• EF70-300mm f/4–5.6 IS USM	112–480	91–390	Ultrasonic	34°–8°15'	21°15'–5°24'	27°12'–6°36'	10/15	32–45	58	4.9	1.5	5–7/16	137.2	1.4 lbs.	630	ET-65B	E-58U	LP1222			
• EF75-300mm f/4–5.6 IS USM †	120–480	98–390	Ultrasonic	32°11'–8°15'	20°17'–5°24'	25°46'–6°36'	10/15	32–45	58	4.9	1.5	5–7/16	137.2	1.4 lbs.	650	ET-64II	E-58U	LP1022			
• EF75-300mm f/4-5.6 II USM/III/II USM †	120–480	98–390	MM/Ultrasonic	32°11'–8°15'	20°17'–5°24'	25°46'–6°36'	9/13	32–45	58	4.9	1.5	4–13/16	122.0	1.1 lbs.	480	ET-60	E-58U	LP1019			
• EF75-300mm f/4-5.6 USM	120–480	98–390	Ultrasonic	32°11'–8°15'	20°17'–5°24'	25°46'–6°36'	10/15	32–45	58	4.9	1.5	5–7/16	137.2	1.4 lbs.	650	ET-64II	E-58U	LP1022			
• EF80-200mm f/2.8L	–	–	AFD	–	–	–	13/16	32	72	5.9	1.8	7–5/16	186.2	2.9 lbs.	1,330	ES-79	–	–			
• EF80-200mm f/4-5.6 II †/ USM †	128–320	104–260	MM/Ultrasonic	30°–12°	18°54'–7°34'	24°–9°36'	7/10	22–27	52	4.9	1.5	3–1/8	78.5	8.34	250	ET-54	E-52	LP1014			
• EF100-300mm f/4-5.6L USM	160–480	130–390	Ultrasonic	24°–8°15'	15°7'–5°24'	19°12'–6°36'	10/13	32–38	58	4.9	1.5	4–3/4	121.5	1.2 lbs.	540	ET-65III	E-58U	LP1019			
• EF100-300mm f/5.6 L †	–	–	AFD	–	–	–	10/15	32	58	4.6	1.4	6–9/16	167	1.5 lbs.	695	ET-62II	–	–			
• EF100-400mm f/4-5.6L IS USM	160–640	130–520	Ultrasonic	24°–6°10'	15°7'–3°53'	19°12'–4°56'	14/17	32–38	77	5.9	1.8	7–7/16	189.0	3.0 lbs.	1,360	ET-83C	E-77U	LZ1324			
Wide-Angle																					
• EF14mm f/2.8L II USM	22	18	Ultrasonic	114°	71°49'	91°12'	11/14	22	Gelatin	0.66	0.2	3–3/4	116.0	22.8	645	Built-in	Exclusive	LP1016			
• EF14mm f/2.8L USM	22	18	Ultrasonic	114°	71°49'	91°12'	10/14	22	Gelatin	0.8	0.25	3–1/2	89.8	1.2 lbs.	560	Built-in	Exclusive	LP1016			
• EF15mm f/2.8 Fisheye	24	20	AFD	180°	113°24'	144°	7/8	22	Gelatin	0.7	0.2	2–7/16	62.2	11.6	330	Built-in	E-73	LP814			
• EF20mm f/2.8 USM	32	26	Ultrasonic	94°	59°13'	75°12'	9/11	22	72	0.8	0.25	2–13/16	70.6	14.3	405	EW-75II	E-72U	LP1214			
• EF24mm f/1.4L USM	38	31	Ultrasonic	84°	52°55'	67°12'	9/11	22	77	0.82	0.25	3	77.4	1.2 lbs.	550	EW-83DII	E-77U	LP1214			
• EF24mm f/2.8	38	31	AFD	84°	52°55'	67°12'	10/10	22	58	0.8	0.25	1–7/8	48.5	9.5	270	EW-60II	E-58	LP811			
• EF28mm f/1.8 USM	45	36	Ultrasonic	75°	47°15'	60°	9/10	22	58	0.8	0.25	2–3/16	55.6	10.9	310	EW-63II	E-58U	LP814			
• EF28mm f/2.8	45	36	AFD	75°	47°15'	60°	5/5	22	52	1.0	0.3	1–11/16	42.5	6.5	185	EW-65II	E-52	LP1011			
• EF35mm f/1.4L USM	56	45	Ultrasonic	63°	39°41'	50°24'	9/11	22	72	0.98	0.3	3–2/5	86.0	1.3 lbs.	580	EW-78C	E-72U	LP1214			
• EF35mm f/2	56	45	AFD	63°	39°4																